


SPECIFICATIONS

Rated Current:2.0AMP
Contact Resistance:20mΩMax
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩMin
Operation Temperature:-40°C to +105°C

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PBT
Max.Processing Temp: 230°C±5°C 5S

Ordering Information

HC-JP 200 - 1 - ** - ** - * - **

No. of Rows
1=Single Type

Length
(mm)
35=3.5mm
50=5.0mm

Type
OP=Open
CL=Close

Color
B=Black
L=Blue
R=Red
W=White
Y=Yellow
V=Green

Contact Plating
G0:Gold Flash
G1:1u" Gold
G2:3u" Gold
G3:5u" Gold
G4:10u" Gold
G5:15u" Gold
G6:30u" Gold
S0:Gold Flash/Tin
S1:Tin

			GENE RL TOL E RANCE		制 图 DRAWING	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审 核 CHECK					
			X. X	± 0.30	批 准 APPROVAL	产品名称 TITLE	2.00 跳线帽 (闭口)	版 本 REV.	A	
1	初版发行		X. XX	± 0.20		产品料号 PART NO.	HC-JP200-1-50-CL-B-XX	单 位 UNITS	mm	
		X. XXX	± 0.10							
序号 No.	变更内容 MODIFY CONTENT	日 期 MODIFY DATE	Angle	± 3.0°	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1