

Live Product Chat

Check Pricing & Availability

Contact Us About This Product

Quick Links

Search for Tooling Product Feature Selector

Products

Documentation

Resources

My Account

Customer Support

Home > Products > By Type > Data Interconnect > Product Feature Selector > Product Details

1-5353576-2 Product Details



1-5353576-2

Universal Serial Bus (USB) Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

- **Product Highlights:** • Size = Standard
- A Series
- Receptacle
- Without Locking Feature
- 1 Ports

View all Features

TE Internal Number: 1-5353576-2 Active









Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

None Available

Product Specifications:

• None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Size = Standard
- Gender = Receptacle
- Number of Ports = 1
- Orientation = Right Angle
- PCB Thickness (mm [in]) = 1.00 [0.039]
- Number of Positions = 4

Mechanical Attachment:

• Mount Location = Bottom

Electrical Characteristics:

• Panel Ground Type = M2 Threaded Hole

Termination Related Features:

• Termination Method = Solder

Body Related Features:

Series = A

Careers

- Locking Feature = Without
- LED = Without
- <u>Panel Ground</u> = With
- PCB Retention Method = SMT Hold Down
- Shell Plating = Bright Tin
- Assembly Process Feature = Pick and Place Cover
- Locating Post(s) = With

Contact Related Features:

- Contact Termination Type = Surface Mount
- <u>Contact Plating</u>, <u>Mating Area</u>, <u>Material</u> = Gold or Gold Flash over Palladium Nickel
- Contact Plating, Mating Area, Thickness = 30 Microinches

Housing Related Features:

• <u>Housing Color</u> = Black

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245?C, Reflow solder capable to 260?C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Terminate To = Printed Circuit Board

Packaging Related Features:

- Panel Ground Location = Right/Left
- <u>Packaging Method</u> = Tray

Other:

• Brand = AMP

Corporate Information Quick Links Customer Support Who We Are Check Distributor Inventory Email or Chat with Us Investors Cross Reference Find a Phone Number Find Documents & Drawings **News Room** Search Knowledge Base Manage Your Account

Supplier Portal **Product Compliance Support Center**

Site Map

© 2009 Tyco Electronics All Rights Reserved | Privacy Policy

