

1

2

3

4

5

REV.	DESCRIPTION	ECN NO.	NAME	DATE

LOCK CARD TATUS

OPEN CARD TATUS

MICRO SIM

一、材质和镀涂:

1. 胶芯: LCP,UL 94V-0,黑色
2. 端子: 磷铜C5210-H,T=0.15, 全区镀底30u"MIN 触点镀金GOLD FLASH0.6-1.0u" 焊脚双面镀亮锡50-80u"
3. 定位脚: 磷铜C2680-H,T=0.20, 全区镀底30u"MIN,镀亮锡50-80u"
4. 外壳: 不锈钢 T=0.2

二、技术参数:

接触电阻: 100MΩ MAX

绝缘阻抗: 1000MΩ MIN(500DC)

额定电流: 每个接触件1A MAX

额定电压: 30V MAX(DC)

耐压: 500V R.M.S/MIN

使用温度: -40℃~85℃

湿度: 80% R.H MAX

寿命: >3000次

PIN NO.	NAME	PIN NO.	NAME
C1	VCC	C4	VPP
C2	GND	C5	CLK
C3	RST	C6	I/O

RECOMMENDED PCB LAYOUT

GENERAL TOLERANCE ±0.05

PIN NO.	NAME	PIN NO.	NAME
C1	VCC	C4	VPP
C2	GND	C5	CLK
C3	RST	C6	I/O

GENERAL TOLERANCE

DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD

TITLE: MICRO SIM CARD HINGED 6PIN H1.8 微盖式

DWG. NO.: SIM201-GZ6PH15

DRAWN: MAX

PART NO.: SIM201-GZ6PH15

CHECKED: ELLA

UNIT: mm

SCALE: none

SHEET: 1 of 1

DWG. SIZE: A4


LAYER: bxconn

APPROVED: WILL

GENERAL TOLERANCE ± 0.05

PIN NO.	NAME	PIN NO.	NAME
C1	VCC	C4	VPP
C2	GND	C5	CLK
C3	RST	C6	I/O

MICRO SIM CARD	
Pin No.	NAME
C1	VCC OF SIM
C2	RST OF SIM
C3	CLK OF SIM
C5	GND OF SIM
C6	VPP OF SIM
C7	I/O OF SIM
C4/C8	N/A

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD					
DIM. TOL. X X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 GENERAL ANGLE: ±3°		TITLE: MICRO SIM CARD HINGED 6PIN H1.8 掀盖式					
		DWG. NO.: SIM201-GZ6PH15		DRAWN: MAX			
		PART NO.: SIM201-GZ6PH15		CHECKED: ELLA			
		UNIT: mm	SCALE: none	SHEET: 1 of 1	DWG. SIZE: A4	LAYER: bxconn	APPROVED: WILL

