


ULTRA MICRO POWER SYSTEM

(2.00 mm) .0787" PITCH



MAX

18
A m p s

FEATURES & BENEFITS

- Board-to-board, cable-to-board and cable-to-cable
- Up to 18 A per blade (1 blade powered)
- Choice of 2 to 10 positions
- 5 mm to 20 mm stack heights; vertical and right-angle orientations
- Tin or 10 μ " Gold plated power blades; 30 μ " Gold plating available to meet specific regulations
- Optional weld tabs
- Mating cable assemblies with plastic top or metal side latching
- Severe Environment Testing qualified (UMPT/UMPS); aligns with MIL-DTL-55302. Visit samtec.com/set

KEY SPECIFICATIONS (UMPT/UMPS)

STACK HEIGHTS	INSULATOR MATERIAL	CONTACT MATERIAL	PLATING	OPERATING TEMP RANGE	VOLTAGE RATING	LEAD-FREE SOLDERABLE
5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 18, 20 mm	Black LCP	Copper Alloy	Sn or Au over 50 μ " (1.27 μ m) Ni	-55 °C to +105 °C with Tin -55 °C to +125 °C with Gold	460 VAC/ 650 VDC	Yes

CURRENT RATING (PER CONTACT)

UMPT/UMPS		
PINS	-T	-L
1	17.8 A	17.5 A
2	15.5 A	16.3 A
3	13.5 A	13.9 A
4	12.9 A	13.2 A
10	9.8 A	8.9 A

Ratings are derated 20% with 30 °C rise to maximum allowable temperature.

CREEPAGE & CLEARANCE

UMPT/UMPS	
CREEPAGE	2.20 mm
CLEARANCE	1.65 mm

Selectively loading contacts achieves customer specific creepage and clearance requirements.

ULTRA MICRO POWER SOCKET



UMPS	NO. OF POSITIONS	LEAD STYLE	PLATING OPTION	V	S	OPTION	"X"R
	-02, -03, -04, -05, -06, -07, -08, -09, -10	-03.5 = (03.5 mm) .138" -05.5 = (05.5 mm) .217" -07.5 = (07.5 mm) .295"	-L = 10 μ " (0.25 μ m) Gold on contact, Matte Tin on tail -S = 30 μ " (0.76 μ m) Gold on contact, Matte Tin on tail -T = Matte Tin			-W = Weld Tab Through-hole (Leave blank for no weld tab)	-TR = Tape & Reel -FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks)

UMPS
Board Mates:
UMPT
Standoffs:
GPSO



NO. OF POSITIONS	A	B	C
-02	(9.05) .356	(7.65) .301	(6.00) .236
-03	(11.05) .435	(9.65) .380	(8.00) .315
-04	(13.05) .514	(11.65) .459	(10.00) .394
-05	(15.05) .593	(13.65) .537	(12.00) .472
-06	(17.05) .671	(15.65) .616	(14.00) .551
-07	(19.05) .750	(17.65) .695	(16.00) .630
-08	(21.05) .829	(19.65) .774	(18.00) .709
-09	(23.05) .907	(21.65) .852	(20.00) .787
-10	(25.05) .986	(23.65) .931	(22.00) .866

LEAD STYLE	D
-03.5	(4.15) .163
-05.5	(6.15) .242
-07.5	(8.15) .321



UMPS-04-03.5-X-V-S-W SHOWN

UMPT/UMPS CURRENT RATING (PER CONTACT)

PINS	-T	-L
1	17.8 A	17.5 A
2	15.5 A	16.3 A
3	13.5 A	13.9 A
4	12.9 A	13.2 A
10	9.8 A	8.9 A

Ratings are derated 20% with 30 °C rise to maximum allowable temperature.

Notes:
Severe Environment
Testing qualified; aligns
with MIL-DTL-55302.
Visit samtec.com/set

Some lengths, styles and
options are non-standard,
non-returnable

View complete specifications at: samtec.com?UMPS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[UMPS-03-03.5-G-VT-SM-WT-K](#) [UMPS-04-03.5-G-VT-SM-WT-K](#) [UMPS-04-05.5-G-VT-SM-WT-K](#) [UMPS-02-03.5-G-VT-SM-WT-K](#) [UMPS-02-05.5-G-VT-SM-WT-K](#) [UMPS-04-03.5-G-VT-SM-K](#) [UMPS-05-03.5-G-VT-SM](#) [UMPS-04-05.5-T-VT-SM](#) [UMPS-05-03.5-G-VT-SM-WT](#) [UMPS05035GVSTR](#) [UMPS05035GVSWTR](#) [UMPS05055GVSWTR](#) [UMPS-05-03.5-G-V-S-TR](#) [UMPS-05-03.5-G-V-S-W-TR](#) [UMPS-05-05.5-G-V-S-W-TR](#) [UMPS-02-03.5-L-V-S-W-TR](#) [UMPS-02-05.5-L-V-S-W-TR](#) [UMPS-02-07.5-L-V-S-W-TR](#) [UMPS-03-03.5-L-V-S-W-TR](#) [UMPS-03-05.5-L-V-S-W-TR](#) [UMPS-03-07.5-L-V-S-W-TR](#) [UMPS-04-03.5-L-V-S-W-TR](#) [UMPS-04-05.5-L-V-S-W-TR](#) [UMPS-04-07.5-L-V-S-W-TR](#) [UMPS-06-03.5-L-V-S-W-TR](#) [UMPS-06-05.5-L-V-S-W-TR](#) [UMPS-06-07.5-L-V-S-W-TR](#) [UMPS-10-03.5-L-V-S-W-TR](#) [UMPS-10-05.5-L-V-S-W-TR](#) [UMPS-10-07.5-L-V-S-W-TR](#) [UMPS-02-03.5-G-V-S-W-TR](#) [UMPS-02-05.5-G-V-S-TR](#) [UMPS-02-05.5-G-V-S-W-TR](#) [UMPS-03-03.5-G-V-S-W-TR](#) [UMPS-03-03.5-T-V-S-W-TR](#) [UMPS-03-05.5-G-V-S-W-TR](#) [UMPS-04-03.5-G-V-S-TR](#) [UMPS-04-03.5-G-V-S-W-TR](#) [UMPS-04-05.5-G-V-S-W-TR](#) [UMPS-04-05.5-T-V-S-TR](#) [UMPS02035GVSWFR](#) [UMPS02035LVSTR](#) [UMPS02035LVSWFR](#) [UMPS02035TVSTR](#) [UMPS02035TVSWFR](#) [UMPS02035TVSWTR](#) [UMPS02055LVSFR](#) [UMPS02055LVSTR](#) [UMPS02055TVSWTR](#) [UMPS02075GVSWTR](#) [UMPS03035GVSTR](#) [UMPS03055GVSWFR](#) [UMPS03055SVSWFR](#) [UMPS03055SVSWTR](#) [UMPS04035GVSFR](#) [UMPS04035GVSWFR](#) [UMPS04035LVSFR](#) [UMPS04035LVSTR](#) [UMPS04035SVSFR](#) [UMPS04035SVSTR](#) [UMPS04035SVSWTR](#) [UMPS04035TVSFR](#) [UMPS04035TVSTR](#) [UMPS04035TVSWTR](#) [UMPS04055GVSTR](#) [UMPS04055LVSFR](#) [UMPS04055LVSTR](#) [UMPS04055SVSTR](#) [UMPS04055TVSWTR](#) [UMPS04075GVSWTR](#) [UMPS04075LVSTR](#) [UMPS04075TVSTR](#) [UMPS05035GVSFR](#) [UMPS05035GVSWFR](#) [UMPS05035LVSTR](#) [UMPS05035LVSWFR](#) [UMPS05035LVSWTR](#) [UMPS05035SVSFR](#) [UMPS05035SVSTR](#) [UMPS05035SVSWFR](#) [UMPS05035SVSWTR](#) [UMPS05035TVSWTR](#) [UMPS05055GVSTR](#) [UMPS05055LVSWFR](#) [UMPS05055LVSWTR](#) [UMPS05055SVSFR](#) [UMPS05055SVSTR](#) [UMPS05055SVSWFR](#) [UMPS05055SVSWTR](#) [UMPS05055TVSTR](#) [UMPS05055TVSWFR](#) [UMPS05055TVSWTR](#) [UMPS05075TVSWTR](#) [UMPS06035GVSFR](#) [UMPS06035GVSTR](#) [UMPS06035LVSFR](#) [UMPS06035LVSTR](#) [UMPS06055GVSWTR](#) [UMPS07055GVSWTR](#) [UMPS07055LVSFR](#)