




RoHS




RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

Specifications/技术规格:

- 1.Current rating/额定电流: 0.5A
- 2.Voltage rating/额定电压: 50V DC
- 3.Insulation Resistance/绝缘电阻: 100MΩ Min
- 4.Dielectric Withstanding/ 耐电压: 500V AC/minute
- 5.Contact Resistance/ 接触电阻: 100mΩ Max
- 6.Durability/ 耐久性: 5,000 Insertions
- 7.Operating Temperature/ 工作温度: -25℃ to +85℃

SIM pin assignment	
PIN#	Name
C1	VCC供电电压
C2	RST重置
C3	CLK时钟
C5	GND接地
C6	VPP程序电压
C7	I/O输入输出



STEP 1 INSERT NANO SIM CARD



STEP 2 PUSH THE SHELL

⑤	Terminal		3	Phosphor bronze	Au plated
⑥	Contact		6	Phosphor bronze	Au plated
⑦	Cover		1	SUS	Ni Plating
⑧	Base		1	LCP	Black
NO.	Name	Number	Qty	Materil	Remarks
YUANDI® Yuandi Electronics Co.,Ltd					
design		date	name	NANO SIM CARD CONNECTOR	
Review		date			
Approved		date			
number:			model	NANO-SIM-507	
mm	1:1	unit	mm	gape number	A4
					