




TECHNICAL SPECIFICATION

INSULATOR MATERIAL	: SELF EXTINGUISHING THERMOPLASTIC (UL94 VO)
CONTACT MATERIAL	: COPPER ALLOY
MAXIMUM VOLTAGE	: 500 V rms.
NOMINAL CURRENT	: 3A AT 20°C
INSULATION RESISTANCE	: $\geq 1000 \text{ M}\Omega$
CLIMATIC CATAGORY	: -55°C TO +125°C / 21 DAYS EXPOSURE TO— INDUSTRIAL ENVIRONMENT HUMIDITY TEST AS HE-14.
CONTACT RESISTANCE	: $\leq 20\text{m}\Omega$

NOTES :
1. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-004

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[861410021H12](#) [861410021H12LF](#) [861410021H110BL](#) [861410021H110BLLF](#) [861410021H110LF](#) [861410021H11BL](#)
[861410021H11BLLF](#) [861410021H16](#) [861410021H16LF](#)