





RoHS



SIM pin assignment	
PIN#	Name
C1	VCC供电电压
C2	RST重置
C3	CLK时钟
C5	GND接地
C6	VPP程序电压
C7	I/O输入输出



Specifications/技术规格:

- 1.Current rating/额定电流: 0.5A
- 2.Voltage rating/额定电压: 125V AC/DC
- 3.Insulation Resistance/绝缘电阻: 100M Ω Min
- 4.Dielectric Withstanding/ 耐电压: 500V AC/minute
- 5.Contact Resistance/ 接触电阻: 100m Ω Max
- 6.Durability/ 耐久性: 5,000 Insertions
- 7.Operating Temperature/ 工作温度: -40 $^{\circ}$ C to +85 $^{\circ}$ C


①	Terminal		6	Phosphor bronze	Au plated
②	Contact		6	Phosphor bronze	Au plated
③	Cover		1	SUS	Ni Plating
④	Base		1	LCP	Black
NO.	Name	Number	Qty	Materil	Remarks
ZHONGDI® Zhongdi Electronic Technology Co., Ltd 					
design		date		name	NANO SIM CARD CONNECTOR
Review		date		model	NANO-SIM-0501-P
Approved		date			
number:					
or 1:1	unit	mm	gape number	A4	

RoHS

User Direction of Unreeling
User Direction of Unreeling

NOTES

1. NUMBER OF CONNECTORS:1800PCS/REEL
2. LEAD TAPE LENGTH



3. QUANTITY:18000PCS/CARTON

COVER TAPE PEELING ANGLE:165°~180°
PEELING FORCE:20~130g

CARRIER TAPE

User Direction of Unreeling

DETAIL B

DETAIL B

10-REEL

TAPE ON

ZHONGDI®

Zhongdi Electronic Technology Co., Ltd

design	date	name	NANO SIM CARD CONNECTOR
Review	date	model	NANO-SIM-0501-P
Approved	date		

Drawing number: Proportion 1:1 unit mm gape number A4

modify Review Approved

Tolerance not specified